

IP/SIP Network Paging Microphone with Intercom

Features:

- ▶ Professional IP/SIP Call Station to control and make announcement to all devices in the system.
- ▶ Adopt high-speed industrial grade chip, startup in less than 1s
- ▶ Support zone paging, and the red indicator will light up when talking
- ▶ Built-in speaker for monitoring and intercom
- ▶ With audio output for external active speaker
- ▶ With audio input for external audio source to target terminals
- ▶ Support offline talkback (without server)

Model with prefix "S" means SIP version



IPM-20/SIPM-20

IPM-30

Model	IPM-20/SIPM-20 (Button version)	IPM-30
Network Communication Protocol	IP, ARP, ICMP, DHCP, UDP, DNS, IGMP(SIP for SIPM-20)	IP, ARP, ICMP, DHCP, UDP, DNS, IGMP
Network Interface	10/100Base-TX, RJ45	10/100Base-TX, RJ45
Frequency and Sampling Rate	8kHz-32 kHz, 16 bit	8kHz-32 kHz, 16 bit
Decoding	MPEG,ADPC	MPEG,ADPC
Microphone Frequency Range	70Hz~12.5KHz	70Hz~12.5KHz
Operating Temp.	0~65°C	0~65°C
Screen	TFT 2.8" LCD	7" touch screen
Power Supply	DC 12V	DC 12V
Dimension	210 x 145 x 55 mm	250 x 145 x 55 mm