



Desktop Smart Video SIP Phone with Android System

Description:

SIP-T06 provides complete desk phone solutions with flexible functionality, HD Voice Quality, and highly easy operation. It is absolutely an excellent Smart Video Phone for small to large sized business, as well as mission-critical Enterprise Business.

Features:

- ▶ Support 6 SIP lines, 3-way conferencing
- ▶ POE enabled, optional external power supply
- ▶ Support Handset / Hands-free / Headset mode
- ▶ Supports third party communication APP
- ▶ Full Programmable DSS Keys and soft function Keys
- ▶ DSS can support up to 140 Stations
- ▶ Online recording & message forwarding
- ▶ Call conference enhancement
- ▶ Flexible dial plan with auto provision
- ▶ Support LDAP & XML phone book
- ▶ High Interoperability – Compatible with major platforms: 3CX, Asterisk, Broadsoft, Elastix, Zycoo, etc.



Model	SIP-T06
Networking	10/100/1000Mbps Ethernet, dual bridged port for PC bypass
IP Configuration	Static / DHCP / PPPoE
Protocols	SIP2.0 over UDP/TCP/TLS; RTP/RTCP/SRTP; STUN; DHCP; LLDP; PPPoE; 802.1x; L2TP; OpenVPN; SNTP; FTP/TFTP; HTTP/HTTPS; TR-069
Physical Ports	
RJ9 Port x2	Handset x1, Headphone x1
RJ45 Port x2	Network x1, PC x1 (Bridged to Network)
HDMI Port x1	Type A
USB 2.0 Port x2	Mini-B x1, Connect with Flash Driver Standard A x1, Connect with BT USB dongle or Flash Driver
TF card slot x1	TF Card Support Up to 32G
Keypad	5 keys (Headset, Menu, Hands-free, Back, Home)
Screen	7 inch (800x480) capacitance color-screen LCD
Operation System	Android 4.2.2 OS
Video Format	MP4/3GP/FLV
Video CODEC	H.263/H.264
Bandwidth Selection	64kbps ~ 4Mbps
Frame rate Selection	10 ~ 30fps
Audio format	WAV/MP3/OGG
Narrowband CODEC	G.711a/u, G.723.1, G.729AB, AMR, iLBC
Wide band CODEC	G.722
Image format	JPEG/PNG/BMP/GIF
Installation	Desktop Stand or Wall-mount
DC Power Input	12V/1A
Power Consumption	Idle 2.5W/Active 5W
Dimensions	Desktop Stand (angles 1): 254.8x154.9x202.8mm Desktop Stand (angles 2): 254.8x167.8x182.4mm Wall-mount: 254.8x118.4x206.9mm
Gift Box Dimensions	290x260x73mm
Outer CTN Dimensions	540x385x310mm (10 PCS)