



### High Power Amplifier D-AMP1000 D-AMP1500

#### Features:

- ▶ Ranging from 1000W to 1500W power capacity.
- ▶ Reliable and mature technology prevent device from overheat.
- ▶ Selectable output: 100V, 70V and 4-16 Ohm.
- ▶ Loudspeaker output with short circuit protection.



SPECIFICATIONS	D-AMP1000	D-AMP1500
Rated Power Output	1000W	1500W
Output Regulation	Less than 3 dB (no load to full load)	
Speaker Output	4.9 ohms (70V), balanced 10.0 ohms (100V), balanced Low impedance: 4-16 ohms, balanced	3.3 ohms (70V), balanced 6.7 ohms (100V), balanced Low impedance: 4-16 ohms, balanced
Input	Less than 1V, unbalanced, XLR and phone jack	
Output	775V, 0dB, XLR and phone jack	
Frequency Response	50 - 18,000 Hz, +/- 1.5dB	
THD	Less than 0.5% at 1kHz (1/3 Rated Power)	
S/N Ratio	Better than 105dB	
Slew Rate	40V/uS	
Controls	Volume control and power switch	
Cooling	Internal 12VDC fan, extensive heat sinking	
Indicators	Power, Clip, Signal, Protect, and Temp LEDs	
Protection	AC Fuse: 20A Current limiter, short circuit and thermal protection circuits	AC Fuse: 25A Current limiter, short circuit and thermal protection circuits
Power Consumption	1350W	2000W
Power Requirments	AC 220V ± 10% 50-60Hz	
Dimensions	133(H) x 486(W) x 483(D) mm	
Net Weight	25.8kg	25.8kg
Gross Weight	28.1kg	38.1kg