



## Out Door Column Speaker

- ▶ Heavy duty aluminum column speaker for outdoor application with high IP rating.
- ▶ Excellent frequency response
- ▶ 70-100V transformer input

IP 44 for outdoor use



Bottom



LM-510T

LM-520T


LM-530T

LM-540T

MODEL	LM-510T	LM-520T	LM-530T	LM-540T
Power at 100V	5/10W	10/20W	15/30W	20/40W
Power at 70V	2.5/5W	5/10W	7.5/15W	10/20W
SPL( 1W/1M)	91dB	91dB	92dB	92dB
Max SPL@ 1M	100dB	103dB	104dB	107dB
Freq. Response	130Hz-16KHz	130Hz-16KHz	130Hz-18KHz	130Hz-16KHz
Dispersion Angel	90x90 degree	90x90 degree	90x80 degree	90x80 degree
Product Size	270x115x150mm	390x115x150mm	505x115x150mm	620x115x150mm
Installation	Wall mounted	Wall mounted	Wall mounted	Wall mounted
Enclosure Material	Aluminum	Aluminum	Aluminum	Aluminum
Weight	2.6Kg	4.1Kg	4.4Kg	5Kg
Finish	Light Grey	Light Grey	Light Grey	Light Grey
Speakers	1" x1 (TREBLE) 4"x1(BASS)	1" x1 (TREBLE) 4"x2(BASS)	1" x1 (TREBLE) 4"x3(BASS)	1" x1 (TREBLE) 4"x4(BASS)

## In- Door Column Speaker

- ▶ Indoor column speaker with slim body to produce good music effects
- ▶ Excellent frequency response
- ▶ 70-100V transformer input



Rear



LM-210

LM-220

LM-230

LM-240

MODEL	LM-210	LM-220	LM-230	LM-240
Power at 100V	5/10W	10/20W	15/30W	20/40W
Power at 70V	2.5/5W	5/10W	7.5/15W	10/20W
SPL( 1W/1M)	90dB	90dB	92dB	92dB
Max SPL@ 1M	100dB	102dB	104dB	107dB
Freq. Response	160Hz-16KHz	160Hz-16KHz	130Hz-18KHz	130Hz-16KHz
Dispersion Angel	90x100 degree	90x110 degree	90x110 degree	80x110 degree
Product Size	260x105x75mm	405x105x75mm	548x105x75mm	690x105x75mm
Installation	Wall mounted	Wall mounted	Wall mounted	Wall mounted
Enclosure Material	Aluminum	Aluminum	Aluminum	Aluminum
Weight	1.3Kg	2Kg	2.7Kg	3.5Kg
Finish	White	White	White	White
Speakers	2.5" x2 full range	2.5" x4 full range	2.5" x6 full range	2.5" x8 full range