

Pre- Amplifier AL-11P

With multi versatile inputs

Features:

- ▶ The AL-11P is a versatile mixer pre-amplifier with 4 microphone inputs, 3 auxiliary inputs, 2 emergency inputs (high priority) and mute function.
- ▶ MIC1, EMC1, EMC2 are priority inputs, automatically muting all other signal inputs. MIC1 has the highest priority, able to suppress all other inputs.
- ▶ With bass and treble control, automatic mute function for paging and individual gain control for all the inputs.



SPECIFICATIONS AL-11P

Input	MIC 1, 2, 3, 4: 600 ohms, 5mV, unbalanced, phone jack AUX 1, 2, 3: 10k ohms, 200mV, unbalanced, RCA jack EMC 1, 2: 10k ohms, 200mV, unbalanced, phone jack
Output	600 ohms, 775mV, 0 dB, RCA jack
Frequency Response	60Hz – 15kHz (+/- 3dB)
S/N Ratio	Better than 70dB
THD	Less than 0.1% at 1kHz
Tone Controls	BASS: 100 Hz (+/- 10dB), TREBLE: 12k Hz (+/- 10dB)
Muting Function	MIC1 overrides other input signals with 0.30 dB attenuation EMC1 overrides other input signals except MIC 1
Power Requirements	220–240V AC, 50/60 Hz
Dimensions	89(H) x 483(W) x 366(D) mm

10-CHANNEL MONITOR PANEL AL-10M

Features:

- ▶ With built-in high fidelity loudspeaker monitoring up to 10 zones. 6 LED dB level meter clearly indicate the channel level status.
- ▶ The monitoring volume is adjustable as well as the 10 channel position selection.



SPECIFICATIONS AL-10M

Input	70/100V audio signal
Monitored Channels	10
Audible Monitor	Full-range loudspeaker, 500mW
Visual Monitor	6-element LED display, infinite, 0, 2, 4, 6, 8, 10 dB
Controls	Monitor volume, channel select and power switch
Indicators	Power LED
Protection	AC Fuse: 0.5A
Power Consumption	10–15 watts
Power Requirements	110–120V or 220–240V AC, 50/60 Hz; 24VDC
Dimensions	89(H) x 483(W) x 366(D) mm
Built-in Dimensions	2 U rack 19 inch
Net Weight	6.1kg