



Horn Speaker

H-150D

- ▶ Low impedance Horn Driver
- ▶ Water proof with stainless steel screw for outdoor use
- ▶ Good for Mosque

IP 67



H-100D

- ▶ Low impedance Horn Driver
- ▶ Water proof with stainless steel screw for outdoor use
- ▶ Good for Mosque

IP 67



H-100DT

- ▶ Intelligible Horn Driver
- ▶ Water proof with stainless steel screw for outdoor use
- ▶ With 100W transformer

IP 67



H-60DT

- ▶ High efficient Neodymium magnet
- ▶ Water proof with stainless steel screw for outdoor use
- ▶ With 60W transformer

IP 67



H-30DT

- ▶ Low impedance Horn Driver
- ▶ Water proof with stainless steel screw for outdoor use
- ▶ Good for Mosque

IP 67



MODEL	H-150D	H-100D	H-100DT	H-60DT	H-30DT; H-50DT
Power at 100V	150W@ 16 ohm	100W@ 16 ohm	60/80/100W; 100W@ 16 ohm	20/40/60W; 60W@ 16 ohm	5/10/15/30W; 15/30/50W
Power at 70V	NA	NA	30/40/50W; 100W@ 16 ohm	10/20/30W; 60W@ 16 ohm	2.5/5/7.5/15/30W ; 8/15/25/50W
SPL(1W/1M)	115dB	115dB	113dB	115dB	110dB
Max SPL@ 1M	134dB	132dB	132dB	132dB	124dB;130dB
Freq. Response	160Hz-8KHz	160Hz-8KHz	160Hz-7KHz	150Hz-7KHz	300Hz-5KHz
Product Size	Dia 124x110 mm	Dia 124x110 mm	Dia 163x174 mm	Dia 110x154 mm	Dia 108x132 mm
Installation	Fix to Horn	Fix to Horn	Fix to Horn	Fix to Horn	Fix to Horn
Enclosure Material	Aluminum	Aluminum	Aluminum	Aluminum	Plastic
Weight	2.2Kg	2.2Kg	2.6Kg	2.2Kg	2.1Kg; 2.2Kg
Finish	Grey	Grey	Grey	Grey	Grey

HN-50T

- ▶ Wide range Horn
- ▶ Water proof for any outdoor applications
- ▶ Good for Mosque

IP 67



HI series

- ▶ Horn Housing
- ▶ Work with 13/8-18 TPI thread driver for various applications
- ▶ Available in 20 inch, 22 inch and 24 inch

IP 67



H-400

- ▶ High power 4 drivers speaker
- ▶ Normally use for high demand requirement, like army, ship
- ▶ High sensitivity

IP 67



HE-30T

- ▶ Explosive proof horn
- ▶ Design for hazard environment, like mining, nuclear plant etc.

IP 67

Explosive Proof



MODEL	HN-50T	HI-20, 22, 24	H-400	HE-30T
Power at 100V	7.5/15/30/50W; 50W@ 16 ohm	NA	400W@ 16 ohm	10/15/25W
Power at 70V	3.8/7.5/12.5/25W; 50W@ 16 ohm	NA	NA	5/7.5/15W
SPL(1W/1M)	110dB	NA	117dB	115± 3dB
Max SPL@ 1M	130dB	NA	142dB	NA
Freq. Response	160Hz-8KHz	NA	150Hz-7KHz	350Hz-10KHz
Product Size	Dia 500x470 mm	Dia 20, 22 and 24 inch	Dia 494x522 mm	Dia 250x351 mm
Installation	Bracket	Bracket	Bracket	Bracket
Enclosure Material	Aluminum	Aluminum	Aluminum	ABS
Weight	3.65Kg	NA	8Kg	3.5kg
Finish	Grey	Light Grey	Grey	Black