



PJ-510PEN

- ▶ Elegant outlook
- ▶ Weather proof projector
- ▶ With 2 cable entries
- ▶ With 10W transformer
- ▶ EN 54 Part 24 compliance

IP 55



PJ-520PEN

- ▶ Elegant outlook
- ▶ Weather proof projector
- ▶ With 2 cable entries
- ▶ With 20W transformer
- ▶ EN 54 Part 24 compliance

IP 55



PJ-520MEN

- ▶ Elegant outlook
- ▶ Weather proof projector
- ▶ Steady aluminum enclosure
- ▶ With 2 cable entries
- ▶ With 20W transformer
- ▶ EN 54 Part 24 compliance

IP 55



| MODEL | PJ-510PEN | PJ-520PEN | PJ-520MEN |
|--------------------|---------------------|-------------------------|-------------------|
| Power at 100V | 1.25W/2.5W/5W/10W | 1.25W/2.5W/5W/10W/20W | 2.5W/5W/10W/20W |
| Power at 70V | 0.63W/1.25W/2.5W/5W | 0.63W/1.25W/2.5W/5W/10W | 1.25W/2.5W/5W/10W |
| SPL(1W/1M) | 92dB | 92dB | 93dB |
| Max SPL@ 1M | 102dB | 105dB | 106dB |
| Freq. Response | 130Hz-17KHz | 130Hz-17KHz | 130Hz-17KHz |
| Dispersion Angel | 100degree | 100degree | 100degree |
| Product Size | dia135*205mm | dia135*205mm | dia138*205mm |
| Installation | wall | wall | wall |
| Enclosure Material | ABS | ABS | Aluminum |
| Weight | 1.7KG | 1.8KG | 2.4KG |
| Finish | White | White | White |
| Speakers | 5" *1 full range | 5" *1 full range | 5" *1 full range |

PJ-510M

- ▶ Weather proof projector
- ▶ Steady aluminum enclosure
- ▶ With 10W transformer

IP 55



PJ-620M

- ▶ Weather proof projector
- ▶ Steady aluminum enclosure
- ▶ With 20W transformer

IP 55



PJ-620B

- ▶ Weather proof projector
- ▶ Steady aluminum enclosure
- ▶ With 20W transformer
- ▶ Bi Direction

IP 55 and bi directional



PJ-510P

- ▶ ABS projector
- ▶ Mini size yet powerful sound
- ▶ With 10W transformer
- ▶ Good for PA and BGM

IP 55



| MODEL | PJ-510M | PJ-620M | PJ-620B | PJ-510P |
|--------------------|------------------|--------------------|--------------------|-------------------|
| Power at 100V | 5/10W | 10/20W | 10/20W | 5/10W |
| Power at 70V | 2.5/5W | 5/10W | 5/10W | 2.5/5W |
| SPL(1W/1M) | 91dB | 92dB | 92dB | 91dB |
| Max SPL@ 1M | 100dB | 103dB | 103dB | 100dB |
| Freq. Response | 130Hz-15KHz | 110Hz-15KHz | 110Hz-15KHz | 130Hz-15KHz |
| Dispersion Angel | 100 degree | 120 degree | 320 degree | 100 degree |
| Product Size | Dia 138x205mm | Dia 170x252mm | Dia 170x252mm | Dia 135x 205mm |
| Installation | Wall or ceiling | Wall or ceiling | Wall or corridor | Wall or ceiling |
| Enclosure Material | Aluminum | Aluminum | Aluminum | ABS |
| Weight | 2.2Kg | 2.8Kg | 3.4Kg | 1.5Kg |
| Finish | White | White | White | White |
| Speakers | 5" x1 full range | 6.5" x1 full range | 6.5" x2 full range | 5" x 1 full range |