



## Ceiling Speaker

### CP-510F

- ▶ Ceiling mounted speaker
- ▶ Suitable for the application without false ceiling
- ▶ With 10W transformer



### CP-420

- ▶ ABS Ceiling speaker
- ▶ Water and corrosion proof for outdoor and marine
- ▶ IP 44 Rating



### CP-525

- ▶ ABS Ceiling speaker
- ▶ Water and corrosion proof for outdoor and marine
- ▶ IP 44 rating



MODEL	CP-510F	CP-420	CP-525
Power at 100V	5/10W	20W at 8ohm	25W at 8ohm
Power at 70V	2.5/5W	NA	NA
SPL( 1W/1M)	90dB	88dB	90dB
Max SPL@ 1M	99dB	101dB	103dB
Freq. Response	120Hz-15KHz	155Hz-20KHz	100Hz-20KHz
Cutout Size	N/A	Dia 105mm	Dia 122mm
Product Size	Dia 215mm	Dia 141mm	Dia 165mm
Installation	Ceiling surface mount	Inceiling	Inceiling
Enclosure Material	ABS	ABS	ABS
Weight	1Kg	0.5Kg	0.7Kg
Finish	White	White	White
Speakers	5" x1 full range	1" x1 (TREBLE) 4"x1(BASS)	1" x1 (TREBLE) 5"x1(BASS)

### HG-510P

- ▶ Pendant speaker for the application without a false ceiling
- ▶ Stylish and powerful
- ▶ With 10W transformer



### HG-510PE

- ▶ Spherical loudspeaker
- ▶ Omnidirectional speaker cover 90 degree angel
- ▶ With 10W transformer



### HG-660P

- ▶ Fashion design
- ▶ Wide dispersion angle loud speaker to cover large area
- ▶ With 60W transformer



MODEL	HG-510P	HG-510PE	HG-660P
Power at 100V	2.5/5/10W	5/10W	7.5/10/15/30W/60W
Power at 70V	1.25/2.5/5W	2.5/5W	3.8/5/7.5/15/30W
SPL( 1W/1M)	92dB	90dB	90dB
Max SPL@ 1M	102dB	101dB	106dB
Freq. Response	150Hz-15KHz	100Hz-15KHz	100Hz-18KHz
Dispersion Angel	180x90 degree	160x90 degree	180x360 degree
Product Size	Dia 180mm	Dia 135x205mm	Dia 378mm
Installation	Hang	Hang	Hang
Enclosure Material	ABS	ABS	ABS
Weight	1.4Kg	1.1Kg	2.8Kg
Finish	White	White	White
Speakers	5" x1 full range	5" x1 full range	6" two way speaker