



Dante Speaker: DANTE WP 630 POE

Description

Dante DP PoE Speaker can realize its multifunction the POE power supply or 2 4VDC, audio transmission and signal control via a RJ45 Ethernet port. It can obtain power supply from any Ethernet switch of 802.3 or above standard. Over Dante™ Ethernet that transmits 24-bit audio (44.1K/48KHz) and its control signal can be routed through the Dante™ Controller. All these functions can perform remotely on the PC or Mac by Dante Controller Software.

Ordering Code

DANTE WP 630 POE:

Dante 6-inch Wall speaker with built-in 2x30W amplifier, POE power supply in Pair

DANTE WP 630:

Dante 6-inch Wall speaker with built-in 2x30W amplifier, 24VDC power supply in Pair



MODEL	DANTE WP 630 POE
Input Interface	RJ-45
Audio Input Signal	Dante™ Balanced amplified signal
Cable	Cat-6 or above
Output Power	30W*2
Transmission Rate	100M/1000M bps
Frequency Range	80Hz – 20kHz
Sensitivity	90dB 1w/1m
Sound Pressure Level	108dB (peak)
Total Harmonic Distortion	<0.30%
Signal to Noise Ratio	>100dB
Noise Floor	<200uV
System Efficiency	>70%
Enclosure	ABS
Operation Temperature	-10 to 50 Degree
Color	RAL-9010
Dimension	215*284*190mm
Net Weight	3.5kg