



## CK. Power amplifier

### CK-200/CK-300/CK-500



#### Features:

- ▶ 2U standard
- ▶ Large energy power supply , high-efficiency and super ring transformer
- ▶ Input signal set 0.775V ,1V and 14V selection switch
- ▶ With protection, signal, clip, bridge and power LED
- ▶ Left and right channel with dual polar cooling fan, high- efficiency air cooling channel
- ▶ With a power star soft , DC protection , short protection , thermal protection, overload protection

Model	CK-200	CK-300	CK-500
4Ω load	300Wx2	450Wx2	800Wx2
8Ω load	200Wx2	300Wx2	500Wx2
8Ω bridge load	600W	900W	1000W
Frequency response	20Hz~20kHz ±1dB	20Hz~20kHz ±1dB	20Hz~20kHz ±1dB
SNR	>100dB	>100dB	>100dB
Total Harmonic distortion	<0.01%	<0.01%	<0.01%
Input impedance	20kΩ	20kΩ	20KΩ
Input voltage	0.775V,1,1.4V	0.775V,1,1.4V	0.775V,1,1.4V
Input connect	XLR	XLR	XLR
Output connect	Neutrik Speakon	Neutrik Speakon	Neutrik Speakon
Switch mode	Stereo/Bridge/Parallel	Stereo/Bridge/Parallel	Stereo/Bridge/Parallel
Power supply	220V/240V AC50~60Hz	220V/240V AC50~60Hz	220V/240V AC50~60Hz
Size(L × D × W)mm	480x350x88	480x350x88.9	480x350x88
Weight	10.5kg	13.02kg	14.8kg

