



### Dante 6-Inch Coaxial Ceiling Speaker with POE and DSP

#### Description:

With coaxial two-way drivers, the 60-watt loudspeaker offers rich lows and clear, intelligible highs—along with premium aesthetics that complement any commercial sound installation. DANTE DP 660R POE with DSP features a 6.5-inch woofer and a 1.25-inch coaxial tweeter mounted within the Dispersion Alignment system, delivering a frequency range of 75Hz–20kHz.

#### Features:

- ▶ **High-Quality Audio:** The rimless Dante coaxial ceiling speaker with DSP and PoE delivers exceptional audio quality, ensuring clear and immersive sound reproduction in any space.
- ▶ **Seamless Integration:** Designed with a rimless and discreet profile, this speaker seamlessly blends into any environment, making it an aesthetically pleasing choice for both residential and commercial installations.

- ▶ **Dante Compatibility:** Featuring Dante networking technology, this speaker allows for easy integration into audio-over-IP systems, simplifying audio distribution and control in large-scale installations.
- ▶ **Digital Signal Processing (DSP):** The built-in DSP capabilities enable precise tuning and optimization of audio output, ensuring that sound is tailored to the specific acoustics of the room or venue.
- ▶ **Power over Ethernet (PoE):** With PoE support, this speaker can be powered and connected through a single Ethernet cable, simplifying installation and reducing the need for additional power sources, making it a cost-effective choice.



#### Ordering Code:

**DANTE DP 660R POE with DSP:** Dante 6-inch Coaxial Ceiling Speaker with POE power supply 60W, Rimless front with safety wire, with DSP  
**DP660V:** High performance 6-inch Coaxial Ceiling Speaker with 100W 8OHM; 100V line 80W/40W/20W/10W, Rimless front with safety wire

Model	DANTE DP 660R POE with DSP	DP660V
Speaker Size	1x1" tweeter + 1x6.5" woofer	1x1" tweeter + 1x6.5" woofer
Power at 8ohm	60W (240W, Peak)	100W (400W, Peak)
Power at 100V	/	80W/40W/20W/10W
Power at 70V	/	40W/20W/10W/5W
Sensitivity(1M/W)	91dB	93.1dB
SPL	108dB	111.1dB
Frequency Range	75Hz~20KHz	75Hz~20KHz
Input Interface	RJ45	/
Audio Transmission Protocol	Dante	/
Audio Routing Control	Dante Controller	/
Power Input	802.3af/802.3at/802.3bt compatible	/
Material	Iron+ABS	Iron+ABS
Cutout Size	Dia 176mm	Dia 176mm
Product Size	Dia 316*197mm	Dia 316*197mm
Net Weight	4.5kg	5.2kg
Gross Weight	6.3g	7kg