

**Pendant speaker**
**Features:**

- ▶ Innovative & unique design
- ▶ Wide opening angle
- ▶ Ceiling suspension or wall mount optional
- ▶ With high-quality polypropylene enclosure
- ▶ Adopt acoustic engineering craftsmanship
- ▶ Provide premium performance for demanding applications
- ▶ Suitable for bars, restaurants, retail, education, public facilities, corporate spaces, sport facilities

W: White Color, B: Black Color



**HWS BRC**



**HGS BRC**

Wall mount and ground mount bracket for HWS series 4 inch, 5 inch, and 6 inch; 8 inch not applicable.

Model	HWS-440W/B	HWS-550W/B	HWS-660W/B	HWS-880W/B
Tweeter	0.75" (20 mm) Silk soft dome	1" (25mm) Silk soft dome	1" (25mm) Silk soft dome	1.1" (28 mm) Silk soft dome
Woofer	4" (100 mm) Graphite Cone , Rubber Surround	5" (125mm) Graphite Cone , Rubber Surround	6.5" (165 mm) Graphite Cone , Rubber Surround	8" (203 mm) Graphite Cone , Rubber Surround
Frequency Range+/-3	80 Hz-20k Hz	98 Hz-20k Hz	51 Hz-20k Hz	44 Hz-20k Hz
Power Handling RMS	40W, 8 ohms	50W, 8 ohms	60W, 8 ohms	80W, 8 ohms
Sensitivity	83 dB	84 dB	85 dB	86 dB
Dispersion Angle	110°	/	95°	80°
Taps	8 Ω ,0,20W,10W,5W,2.5W	8 Ω ,0,30W,15W,7.5W,3.75W	8 Ω ,0,40W,20W,10W,5W	8 Ω ,0,50W,25W,12.5W,6.25W
Impedance	8 ohms	8 ohms	8 ohms	8 ohms
Termination	Pluggable Terminal Blocks	Pluggable Terminal Blocks	Pluggable Terminal Blocks	Pluggable Terminal Blocks
Attachment	Brackets/Safety rope	Brackets/Safety rope	Brackets/Safety rope	Safety rope
Dimensions W*H	Dia 155 x 215mm	Dia 190 x 250mm	Dia 230 x 300mm	Dia 270 x 343mm
Certifications	IP66	IP66	IP66	IP66
Material	PP	PP	PP	PP