



24 Slot Charger unit



Features:

- ▶ Powered by AC 110V-220V alternating current (AC).
- ▶ Capable of simultaneously charging 24 receiver units.
- ▶ Equipped with an extendable pull handle and wheels for easy mobility.
- ▶ Features charging protection and indicator functions.

Model	IR-8C
Power Supply	AC110V-220V
Power	66W
Number of Charging Slots	24
Maximum Unit Charging Current	220mA
Charging Time	Approximately 2-2.5 hours
Status Indicators	Red light on - Charging in progress; Green light on - Charging completed
Operating Temperature	0° C-40° C
Dimensions	630 × 370 × 290mm
Net Weight	10.5kg (excluding the battery)

Booster unit for Interpreter unit



The standard cable length from the main control unit to the first interpreter unit is 10 meters. If the actual usage requires a length longer than 10 meters, additional repeaters are needed to extend it, with each added repeater extending the cable length by 10 meters.

Model	IR-8BT
Power Consumption	1.5W
Length of Relay Cable	10m
Operating Temperature	0°C-40°C
Dimensions	120 × 40 × 50mm
Net Weight	211g

Interpreter Booth



Features:

- ▶ Aluminum alloy structure, modular production in the factory.
- ▶ On-site self-assembly, easy and quick assembly, and easy disassembly (installation/dismantling time ≤ 15 minutes).
- ▶ Detachable, mobile, easy to transport, convenient for remote installation, and use, without changing the effectiveness.
- ▶ Lightweight (total weight around 150kg, for 2 people), sturdy and durable.
- ▶ Has good soundproofing and sound absorption functions.

Model	IR-32BOOT
Product Specifications	1.7*1.6*2.0m
Front Window Size	1100*860mm(H)
Side Window Size	680*860mm(H)
Soundproof Window Material	Resin Glass (Glass Thickness 6mm)
Ventilation System	2 Sets of Soundproof Ventilation Systems
Workbench	1140*730*500*mm
Cable Channel	14x5cm(H)
Primary Materials	High-density fireproof sandwich panel Aluminum alloy frame Acrylic glass Ultra-fine environmentally friendly glass wool Flame-retardant sound-absorbing wall felt