



### Compact Outdoor Line Array Speaker

#### Features

- ▶ Controllable coverage features for 60, 45, 30, and 15 degree
- ▶ Ideal for both permanent and temporary installations, including both vertical and horizontal positioning.
- ▶ Equipped with a convenient carrying handle.
- ▶ Can be mounted directly on a wall or suspended by wire, chain or shackle with no need to use optional brackets.
- ▶ Optional mounting brackets allow use in a wide variety of applications, including suspension, ceiling mount, wall mounting, and speaker stand mounting.



Transformer

#### Ordering Code

- LA-200:** 200W outdoor Line array speaker 8 OHM
- LA-200T:** 200W outdoor Line array speaker with Transformer
- LA-200BRC:** LA-200 Ceiling mounting bracket, optional to order
- LA-200BRR:** LA-200 Rigging frame, optional to order
- LA-200BRCB3:** LA-200 Hanging cable 3 Meter\*3, optional to order
- LA-200BRCB5:** LA-200 Hanging cable 5 Meter\*3, optional to order
- LA-200BRCB10:** LA-200 Hanging cable 10 Meter\*3, optional to order

Model	LA-200T	LA-200
Enclosure	Bass-reflex type	
Power at 100V	30/60/120/200W	/
Power at 8ohm	/	200W
Sensitivity (1 W, 1m)	96 dB (60° mode), 97 dB (45° mode), 98 dB (30° mode), 99 dB (15° mode).	
Frequency Response (Deviation-10 dB)	70 to 20,000 Hz(60° mode), 75 to 20,000 Hz(45° mode) 80 to 20,000 Hz(30° mode), 85 to 20,000 Hz(15° mode)	
Crossover Frequency	4 kHz	
Directivity Angle	Horizontal: 100 (over 2,000 Hz) Vertical: 60° (over 800 Hz), 45° (over 1.2 kHz), 30° (over 1.6 kHz), 15° (over 3.2 kHz) variable	
Speaker	Low frequency: 12 cm (5") cone-type x 4 High frequency: Balanced dome-type x 12	
Input Terminal	Two core wire	
Finish (Enclosure)	Polypropylene, white	
Dimensions	408(w) x 546(h) x 342(d) mm	
Color	White/Black	
Weight	18kg	16kg