

**Ultra-Compact Coaxial Two-Way All-weather Horn Speaker**
**Description**

The compact models give systems designers increased flexibility by offering vastly improved music playback, additional coverage patterns and higher output in attractive paintable enclosures. Both models include front-loaded LF drivers in highly reinforced enclosures for natural, non-resonant low frequency reproduction, while identical voicing ensures a uniform listening experience.

**Ordering Code:**

**RC-200: 8 ohm 200W**

**RC-300: 8 ohm 300W**

**RC-200T: 100V line 200W**

**RC-300T: 100V line 300W**

**RC-200 IP : 200W IP Net audio, Powered**

**RC-300 IP : 300W IP Net audio, Powered**

**RC-200 SIP : 200W SIP Net audio, Powered**

**RC-300 SIP : 300W SIP Net audio, Powered**

**Features:**

- ▶ Ultra-compact size, high output
- ▶ Premium music applications
- ▶ full frequency horn, professional, all weather
- ▶ With switch selection 70V, 100V, and 8 ohms
- ▶ With IP, SIP Net audio with our Eco IP system
- ▶ IP 55 for outdoor application



Model	RC-200/RC-200T		RC-300/RC-300T	
Rated power	200W@8ohm	25W/50W/100W/200W@100V 200W@8ohm	300W@8ohm	37.5W/75W/150W/300W@100V 300W@8 ohm
Maximum power	400W		600W	
Input	8ohm	70V/100V/8ohm	8ohm	70V/100V/8ohm
Sensitivity (1W/1M)	103dB ± 3dB		103dB ± 3dB	
Frequency response	70Hz-18KHz		70Hz-18KHz	
Radiation angle	∠90-100°		∠60-120°	
Speaker unit	10"*1(Bass), 1"*1(Treble)		12"*1(Bass),1.5"*1(Treble)	
Product size	385*355*348mm		375*435*395mm	
Weight	13.5KG/15KG		18.5KG/20KG	