



Mixer Amplifier

Description:

The HA series amplifiers are comprehensive, all-in-one desktop type mixer-amplifier solutions for commercial and industrial applications. These low-cost units provide all necessary features in a simple building.

Features:

- ▶ Two line inputs with Euro block and RCA jack.
- ▶ Acceptable wide range input level.
- ▶ 60Watts ~ 500Watts output.
- ▶ Advanced protection system includes current limiting, over current and thermal protections.
- ▶ Desktop type with rack mount bracket
- ▶ Two bands tone controls
- ▶ Low distortion and low noise level
- ▶ Compact size and light weight
- ▶ Ideal commercial and industrial use

Functions:

- ▶ Controls
 - Front: 2 Channel Volume Control & Tone Control .
 - Rear: Parallel selector, 100V/8ohm selector, HPF Switch.
- ▶ Connectors
 - Euro Block for Channel 1-2 Input and link output.
 - RCA for Channel 1-2 Input.
 - Euro Block for Speaker Output.
- ▶ Indicators : Power, Signal, Signal, Clip and Protect.
- ▶ Protection : Current Limiting, Thermal & DC Offset Protection.
- ▶ Cooling : FAN Cooling.



Single Channel



Dual Channels

Model	HA-160/260	HA-1120/2120	HA-1250/2250	HA-1500/2500
Rated Output Power	60W/2x60W	120W/2x120W	240W/2x240W	480W/2x480W
Input sensitivity / Impedance	-0dBu/10kohm Unbalanced / Balanced			
Power Supply Voltage	AC110-240V 50/60Hz			
Power Consumption	105W/195W	195W/360W	325W/635W	588W/1120W
Speaker Output	100V / 8 Ω			
Frequency Response	80Hz~17KHz (+1dB /-3dB)			
S/N Ratio	>80dB (with A-Weight)			
T.H.D	<1% (at rated power, 1kHz)			
Working Humidity	90%			
Output Channel	1 or 2 channel			
Tone Controls	Bass:100Hz(±10dB), Treble:10KHz(±10dB)			
Working Temperature	0°C~+40°C			
Product Dimension (WxHxD)	215*44*330 mm			
Net Weight	3.5kg	3.3kg	3.3kg	3.3kg